

HYDRAULIKHAMMER



Modell		Einsatzgewicht	Länge ca.	Ölbedarf	Betriebsdruck	Meißel-durchmesser	Schlagzahl	Schlagkraft	Schlauch-an-schluß	Bagger-gewicht
		kg	mm	l/min	bar	mm	bpm	joule	inch	ton
Inward Valve Type	NB10	90	850	15~25	80~110	40	800~1200	250	1/2	0.8~2.5
	NB20S	110	1,000	20~30	80~110	45	700~1200	290	1/2	1.2~3.0
	NB30S	150	1,140	25~40	90~120	53	600~1100	320	1/2	2.5~4.5
	NB40S	280	1,678	30~45	95~130	68	500~900	690	1/2	4.0~7.0
	NB43S	375	1,860	40~80	130~150	75	400~800	900	1/2	6~9
	NB50S	818	1,950	80~110	150~170	100	350~700	2100	3/4	11~16
	NB60S	1.355	2,089	90~120	150~170	125	350~650	4000	1	15~18
	NB81S	1.825	2,400	120~150	160~180	140	350~500	5200	1	18~26
	NB130S	2.620	2,600	190~250	160~180	155	250~400	9000	1 1/4	30~40
	NB151S	3.950	3,189	210~290	160~180	175	200~350	14500	1 1/4	40~55
Outward Valve Type	NB18GS	1.310	2,031	90~120	150~180	120	400~900	3200	1	13~18
	NB20GS	1.840	2,327	130~150	160~180	135	400~800	4500	1	18~26
	NB30GS	2.540	2,500	150~190	160~180	150	350~700	7000	1	27~35
	NB40GS	2.950	2,740	190~250	160~180	160	300~600	10000	1 1/4	35~50


NEUMEIER GmbH
www.neumeier-gmbh.com

Boehmerstraße 10, 93437 Furth im Wald /Germany
 Tel. 0049 9973 8466-0, Fax 0049 9973 8466-20
info@neumeier-gmbh.com

